

Rivendell Blériot geometry chart

Size	BB Drop mm	TT Upslope degrees	Rear Hub Space mm	Standover at mid TT cm	ST angle degrees	HT angle degrees	Rake cm	Top Tube cm	Chain stay cm	Wheel size mm	Recommended min. tire radius mm	Recommended max. tire radius mm	Effective brake reach mm	Brake style
49	67	5.8	135	75.1	71	71	5	52.5	44.5	584/650B	312/650x30	338/650x41	65	SP/CP
51	67	3.45	135	76	72	71	5	53.5	44.5	584/650B	312/650x30	338/650x41	65	SP/CP
53	67	2	135	77.5	72	71	5	54.5	44.5	584/650B	312/650x30	338/650x41	65	SP/CP
55	67	2	135	79.4	72	71	5	55.5	44.5	584/650B	312/650x30	338/650x41	65	SP/CP
57	67	2	135	81.3	72	71	5	56.5	44.5	584/650B	312/650x30	338/650x41	65	SP/CP
59	67	2	135	83.2	72	71	5	57.5	44.5	584/650B	312/650x30	338/650x41	65	SP/CP
61	67	2	135	85.1	72	71	5	59	44.5	584/650B	312/650x30	338/650x41	65	SP/CP